




ORDERING INFORMATION

| Part No. | Coil Parameters | | | | Relay Rating | | | | Contact Rating Switching |
|----------|----------------------------|-----------------|--------------------|----------------------|-------------------------------|-------------------------|-------------|-------------------------------------------------------------------------------------|--------------------------------|
| | DC Voltage Maximum Nominal | Maximum Operate | Maximum Continuous | Resistance +10% Ohms | Time (Msecs) Including Bounce | Breakdown Voltage (Vdc) | Switch Form | UL Recognized | |
| 780A301 | 129 | 90 | 152 | 13000 | 3.0 | 1000 | 2A | | 50 W 1.5 A max. 500 Vdc |
| 780A302 | 48 | 30 | 56 | 3200 | 3.0 | 1000 | 2A | | |
| 780A303 | 24 | 15 | 28 | 1600 | 3.0 | 1000 | 2A | | |
| 780A304 | 129 | 90 | 152 | 13000 | 4.0 | 1000 | 1A |  | 100 W 3.0 A max. 300 Vdc |
| 780A307 | 129 | 90 | 152 | 13000 | 4.0 | 1000 | C |  | 50 W 1.0 A max. 250 Vdc |
| 780A308 | 129 | 90 | 152 | 13000 | 0.75 | 750 | 2A |  | 50 W 1.5 A max. 500 Vdc |
| 780A311 | 250 | 180 | 280 | 29000 | 3.0 | 1000 | 2A | | |

Operating Temperature: 0° to 50° Centigrade
 Storage Temperature: -54° to 85° Centigrade
 Altitude Range: 0 to 50,000 feet
 Moisture Resistance: 95% Relative Humidity

Life Expectancy: 1 x 10⁶ Operations Minimum
 Weight: 12 oz maximum Form C, Form A
 14 oz maximum 2 Form A
 Cycling Rate: 60 cps maximum